






View MSDS 9 10 11 12 13 14 15 16 1 <u>5</u> <u>7</u> Section:



SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Foamular® Extruded Polystyrene Insulation

MSDS Manufacturer

Number:

21528-NAM

Synonyms: Foamular® 150, Foamular® 250, Foamular® 350,

Foamular® 400, Foamular® 404, Foamular® 600, Foamular® 604, Foamular® 1000, Foamular® CW15, Foamular® CW25, Foamular® LT30, Foamular® LT40, Foamular® 404RB, Foamular® 604RB, Foamular® AgTek, Foamular® PROPINK®, Foamular®

DURAPINK®, Foamular® PINKCORE®, Foamular® PINKCORE® TT, Foamular® Half-Inch, Foamular® INSULPINK®, Foamular® THERMAPINK®, Foamular® DURAPINK® FA, Foamular® DURAPINK® Plus,

Foamular® INSULPINK® - Z, Foamular®

THERMAPINK® 18, Foamular® THERMAPINK® 25,

Foamular® THERMAPINK® 40, Foamular®

THERMAPINK® 60, Foamular® Extruded Polystyrene, Foamular® Insulating Sheathing, Foamular® INSUL-DRAIN®, Foamular® PinkForm-Xtra; Foamular® OC

LiteForm

Manufacturer Name: Owens Corning Foam Insulation, LLC

Address: One Owens Corning Parkway

Toledo, OH 43659

Customer Service Phone

Number:

1-800-GET-PINK or 1-800-438-7465

Health Issues Information: 1-419-248-8234 (8am-5pm ET) 1-800-GET-PINK or 1-800-438-7465

Technical Product Information:


Emergency Phone Number: 1-419-248-5330 (after 5pm ET and weekends)

CHEMTREC: 800-424-9300 (24 hours everyday)

Canutec: (613) 996-6666 (Canada 24 hours everyday)

Website: www.owenscorning.com

March 05, 1997 MSDS Creation Date: MSDS Revision Date: November 11, 2008





Chronic Health Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name		CAS#	Ingredient Percent
Talc		14807-96-6	0 - 2 by weight
1-Chloro-1, 1-difluoroethane (HCFC-142B)		75-68-3	7 - 12 by weight
Hexabromocyclododecane		3194-55-6	0.5 - 1.5 by weight
Polystyrene		9003-53-6	80 - 90 by weight
Non-Hazardous Statement:.	The remaining components of this product are non-hazardous or are in a small enough quantity as to not meet regulatory thresholds for disclosure. These components contain no substances or impurities which would influence the classification of this product.		

SECTION 3 - HAZARDS IDENTIFICATION

Applies to Product:

Emergency Overview: Dense Black Smoke will be produced during a fire.

Grinding, sawing or fabrication activities can produce dust particles which

under certain conditions may ignite or form explosive dust atmospheres.

Route of Exposure: Eye contact

Inhalation.

Potential Health Effects:

Eye: Dust may cause slight irritation.

Skin: No effects expected.

Inhalation: Dust may cause irritation of respiratory tract.

Ingestion: Ingestion of this product is unlikely.

Chronic Health Effects: There is no known chronic health effect connected with long-term use or

contact with this product.

Carcinogenicity: This material is not considered a carcinogen.

Potential Environmental Effects: There is no known ecological information for this material.

Aggravation of Pre-Existing

Chronic respiratory or skin conditions may temporarily worsen from exposure

Conditions: to this product.

OSHA Regulatory Status: This product is considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

Pink, white or green closed-cell foam board with no odor. Appearance and Odor:

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes.

Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Do not rub or scratch eyes.

If eye irritation persists, consult a specialist.

Immediately wash skin with soap and plenty of water. Skin Contact:

Get medical attention if irritation develops or persists.

Inhalation: Move to fresh air.

If symptoms persist, call a physician.

Ingestion: Accidental ingestion of this material is unlikely.

If this does occur, watch person for several days to make sure intestinal

blockage does not occur.

If symptoms persist, call a physician.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable. Flash Point: > 615 °F (324 °C) Flash Point Method: ASTM D 1929
Auto Ignition Temperature: Not applicable.
Lower Flammable/Explosive Limit: Not applicable.
Upper Flammable/Explosive Limit: Not applicable.
Extinguishing Media: dry chemical

foam

carbon dioxide (CO2)

water fog

Unsuitable Media: None.

Protective Equipment: Wear self-contained breathing apparatus (SCBA) and full fire fighting

protective gear.

Unusual Fire Hazards: Grinding, sawing or fabrication activities can produce dust particles which

under certain conditions may ignite or form explosive dust atmospheres.

Hazardous Combustion Carbon monoxide.

Byproducts:

Carbon dioxide.

styrene.

Small quantities of hydrogen fluoride, hydrogen chloride, fluorine and chlorine

could be released.

Other undetermined compounds could be released in small quantities.

HCFC-142b thermally decomposes at > 430ŰC (850ŰF). Decomposition products include: Hydrogen fluoride, hydrogen chloride, fluorine, and chlorine.

Universal Fire And Explosion

Hazards:

Not available.

NFPA Ratings:

NFPA Health: 0
NFPA Flammability: 1
NFPA Reactivity: 0
NFPA Other:

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Avoid contact with skin and eyes.

Methods for containment: This material will settle out of the air.

Prevent from spreading by covering, diking or other means.

Methods for cleanup: Use an industrial vacuum cleaner with a high efficiency filter to clean up dust.

Avoid dry sweeping.

Pick up and transfer to properly labeled containers. After cleaning, flush away traces with water.

Other Precautions: Does not apply.

SECTION 7 - HANDLING and STORAGE

Handling: Avoid dust formation.

Do not breathe dust.

Wear personal protective equipment.

Storage: Keep product in its packaging until use to minimize potential dust generation.

Product should be kept dry and undercover.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Provide local exhaust and/or general ventilation to maintain exposure below

regulatory and recommended limits.

Dust collection system must be used in transferring operations, cutting or machining or other dust generating processes, such as using power tools.

Vacuum or wet clean-up methods should be used.

Grinding, cutting, sawing or fabrication activities that cut large numbers of interior foam cells can release localized amounts of flammable residual blowing agent or release dust particles that under certain conditions may ignite or form

explosive dust atmospheres.

Eye/Face Protection: Safety glasses with side-shields.

Skin Protection Description: Protective gloves.

Long sleeved shirt and long pants.

Respiratory Protection: When workers are facing airborne particulate/dust concentrations above the

exposure limit they must use appropriate certified respirators.

General Hygiene Considerations: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use.

EXPOSURE GUIDELINES

Guideline OSHA Guideline Guideline Ontario Canada Mexico

NIOSH ACGIH

Talc

REL-TWA: 2
mg/m3
mg/m3
(Respirable)

REL-TWA: 2
TLV-TWA: 2
TWAEV-TWA: 3
TWAEV-TWA: 2
TWAEV-TWA: 2
TWAEV-TWA: 2
TWAEV-TWA: 3
TWAEV-TW

(Respirable) (Respirable) (Respirable) 7 mg/m3, 3 mg/m3,

5 mg/m3, 3 mg/m3, 3 mg/m3,
Respirable, 10 respirable, 10 respirable, 10
mg/m3, Total mg/m3, inhalable mg/m3, inhalable
Particulates Not particles (NOS) Particulates
Otherwise (Insoluble) Not

Classified (PNOC) Otherwise Classified

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State: Solid
Physical State Appearance: Foam.

Color: Pink, white or green
Odor: No detectable odor.

Boiling Point: Decomposes over 600 $\hat{A}^{\circ}F$ (316 $\hat{A}^{\circ}C$)

Melting Point: Softens @ 220 $\hat{A}^{\circ}F$ (104 $\hat{A}^{\circ}C$)

Specific Gravity: 0.021-0.064 (Ref: water = 1).

Solubility: Insoluble in water.

Vapor Density: No Data
Vapor Pressure: No Data
Evaporation Rate: No Data
pH: No Data

Flash Point: $> 615 \ \hat{A}^{\circ}F \ (324 \ \hat{A}^{\circ}C)$

Flash Point Method: ASTM D 1929
Auto Ignition Temperature: Not applicable.

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: Dust dispersion in air.

Incompatible Materials: Hydrocarbons

esters Amines

Special Decomposition Products: See

See Section 5 of MSDS for hazardous decomposition products during a fire.

SECTION 11 - TOXICOLOGICAL INFORMATION

Applies to Product:

Acute Toxicity: Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause

transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. High exposures may

cause difficulty breathing, congestion, and chest tightness.

Carcinogens:

	ACGIH	NIOSH	OSHA	IARC	NTP	MEXICO
Talc	A4 Not Classifiable as a Human Carcinogen	No Data	No Data	Group 2A - Probably carcinogenic to humans.	No Data	A4 Not Classifiable as a Human Carcinogen
1-Chloro-1, 1-difluoroethane (HCFC-142B)	No Data	No Data	No Data	No Data	No Data	No Data
Hexabromocyclododecane	No Data	No Data	No Data	No Data	No Data	No Data
Polystyrene	No Data	No Data No Data Group 3 - Not No Data No Da Classifiable as to its Carcinogenicity to Humans.				No Data

Applies to Product:

Sensitization:

Mutagenicity:

Reproductive Toxicity:

Teratogenicity:

No information available.

Talc:

Skin - Human Standard Draize Test. : 300 ug/3D-I - [mild] (RTECS)

Inhalation: Inhalation. - Rat TCLo: 17 mg/m3/6H/26D (intermittent) [Lungs, Thorax, or

Respiration - other changes]

Inhalation. - Mouse TCLo: 20400 ug/m3/6H/26D (intermittent) [Lungs, Thorax,

or Respiration - other changes]

Inhalation. - Rat TCLo: 18 mg/m3/6H/2Y (intermittent) [Tumorigenic - carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration - bronchiogenic

carcinoma; Endocrine - tumors]

Inhalation. - Rat TC: 11 mg/m3/1Y (intermittent) [Tumorigenic - equivocal tumorigenic agent by RTECS criteria; Lungs, Thorax, or Respiration -

tumors](RTECS)

1-Chloro-1, 1-difluoroethane (HCFC-142B) :

Inhalation: Inhalation. - Mouse LC50: 1758000 mg/m3/2H [Details of toxic effects not

reported other than lethal dose value.

Inhalation. - Rat LC50: 2050000 mg/m3/4H [Details of toxic effects not

reported other than lethal dose value.(RTECS)

<u>Hexabromocyclododecane</u>:

Skin: Skin - Rabbit LD50: >8 gm/kg [Details of toxic effects not reported other than

lethal dose value.](RTECS)

Inhalation: - Rat LD50: >10 gm/kg [Details of toxic effects not reported other

than lethal dose value.](RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Applies to Product:

Ecotoxicity: This material is not expected to cause harm to animals, plants or fish.

Environmental Fate: No data available for this product.

Bioaccumulation: Not available.

Biodegradation: Not available.

Mobility In Environmental Media: Not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Applies to Product:

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial regulations.

Contaminated Packaging: Empty containers should be taken for local recycling, recovery or waste

disposal.

RCRA Number: No EPA Waste Numbers are applicable for this product's components.

RCRA Characteristics: This material is not expected to be a characteristic hazardous waste under

RCRA.

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Not Regulated. IATA Shipping Name: Not Regulated. Canadian Shipping Name: Not Regulated. IMDG Shipping Name: Not Regulated. ADR Shipping Name: Not Regulated. RID Shipping Name: Not Regulated. ICAO Shipping Name: Not Regulated. MEX Shipping Name: Not Regulated.

SECTION 15 - REGULATORY INFORMATION

Inventory	Status
-----------	---------------

_	Japan ENCS	ELINCS	EINECS	PICCS	South Korea
	•		Number		KECL
Talc			238-877-9	Listed	KE-32773
1-Chloro-1, 1- difluoroethane (HCFC-142B)			200-891-8		KE-05597
Hexabromocyclododecane			221-695-9	Listed	KE-18398
Polystyrene	(6)-120	500-008-9			KE-13257

	Austrailia AICS	Canada DSL	EINECS Inventory Status	TSCA Inventory Status
Talc	Listed	Listed	Yes	Listed
1-Chloro-1, 1- difluoroethane (HCFC-142B)	Listed)	Listed	Yes	Listed
Hexabromocyclododecane	Listed	Listed	Yes	Listed
Polystyrene	Listed	Listed	No	Listed

Applies to Product:

Canada Reg. Status: This product has been classified in accordance with the hazard criteria of the

Controlled Products Regulations and the MSDS contains all of the information

required by the Controlled Products Regulations.

Canada WHMIS: Not controlled.

CA PROP 65: The following statement(s) are provided under the California Safe Drinking

Water and Toxic Enforcement Act of 1986 (Proposition 65): This product does not contain any Proposition 65 chemicals.

Section 311/312 Hazard

Categories:Acute Health Hazard:NoChronic Health Hazard:NoRisk of ignition:No

Sudden Release of Pressure Hazard: No Reactive Hazard: No

Clean Air Act: This product does not contain any Hazardous Air Pollutants (HAPs).

1-Chloro-1, 1-difluoroethane (HCFC-142B):

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure

List: 1%. Item: 357(425)

Section 313: Listed

State Right To Know

Talc

All State Information:

1-Chloro-1, 1-difluoroethane (HCFC-142B)

All State Information:

IL PA MA RI MN Listed Listed No Data Listed Listed Talc 1-Chloro-1, 1-No Data No Data No Data Listed Listed difluoroethane (HCFC-142B) No Data No Data No Data No Data No Data Hexabromocyclododecane

Polystyrene No Data No

NJ

Talc No Data 1-Chloro-1, 1- Listed

difluoroethane (HCFC-142B)

Hexabromocyclododecane No Data Polystyrene No Data

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard: 0
HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Personal Protection: X

MSDS Creation Date: March 05, 1997

MSDS Revision Date: November 11, 2008

MSDS Revision Notes: Update in section 4 and 6

Disclaimer: Reasonable care has been taken in the preparation of this information, but the

manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or

consequential damages resulting from its use.

Copyright© 1996-2008 Actio Software Corporation. All Rights Reserved.