
MSDS Format: ANSI







SECTION 1 - IDENTIFICATION

Product Name: Heavy Density Pipe Insulation

MSDS Manufacturer

Number:

18994-SAM-EN

Synonyms: ASJ 25 Pipe Insulation, ASJ/SSL II® Pipe Insulation, Heavy

Density Pipe Insulation, No-Wrap Pipe Insulation, Pipeshield,

SSL® Pipe Insulation, SSL-II® Pipe Insulation, VaporWick®, Vitro Fibras Pipe Insulation, Evolutionâ,¢

Paper-Free ASJ, Aislamiento para Tuberia

Product Use/Restriction: Pipe Insulation

Manufacturer Name: Owens Corning Insulating Systems, LLC

Address: One Owens Corning Parkway

Toledo, OH 43659

Customer Service Phone

Number:

"#ACTIOPHRASE_5027#"

Health Issues Information: 1-419-248-8234 (8am-5pm ET)

Technical Product

Information:

"#ACTIOPHRASE_5027#"

"#ACTIOPHRASE_5027#"

Emergency Phone Number: "#ACTIOPHRASE_5026#"

CHEMTREC: "#ACTIOPHRASE_5024#"

Canutec: "#ACTIOPHRASE_5023#"

Website: www.owenscorning.com

MSDS Creation Date: 05/16/1995 MSDS Revision Date: 01/29/2009



HMIS				
Health Hazard	2*			
Fire Hazard	1			
Reactivity	0			
Personal Protection	х			

* Chronic Health Effects

SECTION 2 - HAZARD(S) IDENTIFICATION

Applies to product :

Emergency Overview: Exposure to dust may be irritating to eyes, nose, and throat.

Route of Exposure: Eye contact

Skin contact Inhalation

Potential Health Effects:

Eye: May cause slight irritation.

Skin: May cause slight skin irritation.

Inhalation: May cause irritation of respiratory tract.

Ingestion: Ingestion of this product is unlikely.

Chronic Health Effects: There is no known chronic health effect connected with long-term use or

contact with this product.

Carcinogenicity: This product contains a component which is listed by IARC, OSHA or NTP. See

Section 11 for additional information.

Potential Environmental Effects: There is no known ecological information for this material.

Aggravation of Pre-Existing Conditions:

Chronic respiratory or skin conditions may temporarily worsen from exposure

ons: to this product.

OSHA Regulatory Status: This product is considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Fiber Glass (Wool)	65997-17-3	60 - 100 by weight
Cured Binder	N/A	0 - 40 by weight

Non-Hazardous Statement:. The remaining components of this product are non-hazardous or are in a small

enough quantity as to not meet regulatory thresholds for disclosure. These components contain no substances or impurities which would influence the

classification of this product.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes.

Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Do not rub or scratch eyes.

If eye irritation persists, consult a specialist.

Skin Contact: Wash off immediately with soap and cold water.

DO NOT use warm water because this will open up the pores of the skin,

which will cause further penetration of the fibers.

Use a wash cloth to help remove fibers. DO NOT rub or scratch affected areas. Remove contaminated clothing.

Remove contaminated clothing.

If irritation persists get medical attention.

Never use compressed air to remove fibers from the skin.

If fibers are seen penetrating from the skin, the fibers can be removed by applying and removing adhesive tape so that the fibers adhere to the tape and

are pulled out of the skin.

Inhalation: Move to fresh air.

If symptoms persist, call a physician.

Ingestion: Accidental ingestion of this material is unlikely.

If this does occur, watch person for several days to make sure intestinal

blockage does not occur.

Rinse mouth with water and drink water to remove fibers from the throat.

If symptoms persist, call a physician.

Note to Physicians: Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable. Flash Point: Does not apply. Does not apply. Auto Ignition Temperature: Extinguishing Media: dry chemical

foam

carbon dioxide (CO2)

water fog

Protective Equipment: Wear self-contained breathing apparatus (SCBA) and full fire fighting

protective gear.

Carbon monoxide

Unusual Fire Hazards: Hydrogen chloride to be released from the PVC barrier and vinyl facings during

a fire.

Hazardous Combustion

Byproducts: Carbon dioxide.

Ammonia.

Other undetermined compounds could be released in small quantities.

Universal Fire And Explosion

Hazards:

Not available.

NFPA Ratings:

NFPA Flammability: 1 NFPA Health: 2 NFPA Reactivity: O NFPA Other:

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Avoid contact with skin and eyes.

Environmental Precautions: Prevent further leakage or spillage if safe to do so.

Methods for containment: This material will settle out of the air.

Prevent from spreading by covering, diking or other means.

Methods for cleanup: Use an industrial vacuum cleaner with a high efficiency filter to clean up dust

and fiber contamination. Avoid dry sweeping.

Pick up and transfer to properly labeled containers.

Other Precautions: Does not apply.

SECTION 7 - HANDLING and STORAGE

Handling: Avoid dust formation.

Do not breathe dust.

Wear personal protective equipment.

Storage: Keep product in its packaging until use to minimize potential dust generation.

Product should be kept dry and undercover.

Hygiene Practices: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Provide local exhaust and/or general ventilation to maintain exposure below **Engineering Controls:**

regulatory and recommended limits.

Dust collection system must be used in transferring operations, cutting or

machining or other dust generating processes, such as using power tools.

Vacuum or wet clean-up methods should be used.

Eye/Face Protection: Safety glasses with side-shields.

Skin Protection Description: Protective gloves.

Long sleeved shirt and long pants.

Respiratory Protection: When workers are facing airborne particulate/dust concentrations above the

exposure limit they must use appropriate certified respirators.

A properly fitted NIOSH approved disposable N 95 type dust respirator or

better is recommended.

Other Protective: When the temperature of the surface being insulated exceeds 250ŰF (121Å

°C), including initial startup, the binder in these products may undergo various degrees of decomposition depending on the temperature in the application. The need for respiratory protection will vary according to the airborne concentration of the decomposition products released and accumulated in the

area.

Wear the appropriate respiratory protection according to the conditions and

exposure levels in the area.

General Hygiene Considerations: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use.

EXPOSURE GUIDELINES

Guideline OSHA Guideline Ontario Canada Mexico

ACGIH

Fiber Glass (Wool) PEL-TWA: 1 f/cc TLV-TWA: 1 f/cc TWAEV-TWA: TWA: 0.15 (Respirable) (Respirable) 0.05 mg/m3 or 1 mg/m3

e) (Respirable) 0.05 mg/m3 or 1 mg/m3 f/cc

STEL: 0.6 mg/m3

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Tan with or without jacket of paper or aluminized plastic film.

Color: Tan

Odor: Faint resin odor.

Boiling Point: No Data
Melting Point: No Data
Specific Gravity: No Data

Solubility: Insoluble in water.

Vapor Density:

Vapor Pressure:

Evaporation Rate:

No Data

No Data

PH:

No Data

No Data

Viscosity:

No Data

Viscosity:

Flash Point:

Does not apply.

Auto Ignition Temperature:

Does not apply.

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: None expected

Incompatible Materials: No materials to be especially mentioned.

Special Decomposition Products: See Section 5 of MSDS for hazardous decomposition products during a fire.

SECTION 11 - TOXICOLOGICAL INFORMATION

Applies to product:

Acute Toxicity:

Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. High exposures may cause difficulty breathing, congestion, and chest tightness.

Carcinogens:

· ·	ACGIH	NIOSH	OSHA	IARC	NTP	MEXICO
Fiber Glass (Wool)	A3 Animal	No Data	OSHA:	Group 3 - Not	RAC -	A3 Animal
	Carcinogen		Designated	Classifiable as to	Reasonably	Carcinogen
			carcinogen	its	anticipated to	
				Carcinogenicity	be a human	
				to Humans.	carcinogen.	
Cured Binder	No Data	No Data	No Data	No Data	No Data	No Data

Applies to product:

Sensitization:

Mutagenicity:

Reproductive Toxicity:

Teratogenicity:

No information available.

Fiber Glass (Wool):

Chronic Effects:

In October 2001, the International Agency for Research on Cancer (IARC) classified fiber glass wool as Group 3,""not classifiable as to its carcinogenicity to humans"". The 2001 decision was based on human studies and animal research that have not shown an association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease. This classification replaces the IARC finding in 1987 of a Group B designation ""possibly carcinogenic to humans."".

In May 1997, the American Conference of Governmental Industrial Hygienists (ACGIH) adopted an A3 carcinogen classification for glass wool fibers. The ACGIH A3 classification considers glass wool to be carcinogenic in experimental animals at relatively high doses, by routes of administration, at sites, or by mechanisms that it does not consider relevant to worker exposure. It also reviewed the available epidemiological studies and concluded that they do not confirm an increased risk of cancer in exposed humans. Overall, the ACGIH found that the available medical/scientific evidence suggests that glass wool is not likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.

Cured Binder:

parasympathomimetic Behavioral - muscle weakness Lungs, Thorax, or

Respiration - respiratory depression]

Inhalation. - Mouse LD50: $\bar{7}$ gm/kg - [Autonomic Nervous System - other (direct) parasympathomimetic Behavioral - muscle weakness Lungs, Thorax, or

Respiration - respiratory depression](RTECS)

Acute Toxicity

SECTION 12 - ECOLOGICAL INFORMATION

Applies to product:

Ecotoxicity: This material is not expected to cause harm to animals, plants or fish.

Environmental Stability: Not available
Environmental Fate: Not available
Bioaccumulation: Not available.
Biodegradation: Not available.
Mobility In Environmental Media: Not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Applies to product:

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial regulations.

Contaminated Packaging: Empty containers should be taken for local recycling, recovery or waste

disposal.

RCRA Number: No EPA Waste Numbers are applicable for this product's components.

RCRA Characteristics: This material is not expected to be a characteristic hazardous waste under

RCRA.

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Not Regulated. IATA Shipping Name: Not Regulated. Canadian Shipping Name: Not Regulated. IMDG Shipping Name: Not Regulated. ADR Shipping Name: Not Regulated. RID Shipping Name: Not Regulated. ICAO Shipping Name: Not Regulated. MEX Shipping Name: Not Regulated.

SECTION 15 - REGULATORY INFORMATION

Inventory Status

	Japan ENCS	EINECS Number	PICCS	China	South Korea
	•				KECL
Fiber Glass (Wool)	Not listed	266-046-0	Listed	Listed	KE-17630
Cured Binder	Not listed			Listed	KE-35185

Austrailia AICS Canada DSL TSCA Inventory

Status

Fiber Glass (Wool) Listed Listed Listed Listed Listed

Applies to product :

Canada Reg. Status: This product has been classified in accordance with the hazard criteria of the

Controlled Products Regulations and the MSDS contains all of the information

required by the Controlled Products Regulations.

Canada WHMIS: Not controlled.

CA PROP 65: The following statement(s) are provided under the California Safe Drinking

Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the State of California to

cause cancer.

SARA: This product does not contain any chemicals which are subject to the reporting

requirements of the Superfund Amendments and Reauthorization Act of 1986

(SARA) Title III (40CFR, Part 372).

Section 311/312 Hazard

Categories: Acute Health Hazard: Yes

Chronic Health Hazard: Yes
Risk of ignition: No
Sudden Release of Pressure Hazard: No
Reactive Hazard: No

Clean Air Act: This product does not contain any Hazardous Air Pollutants (HAPs).

State Right To Know

RI MN IL PA MA Listed Listed Listed Listed Listed Fiber Glass (Wool) No Data No Data No Data No Data No Data Cured Binder

NJ

Fiber Glass (Wool) No Data
Cured Binder No Data

SECTION 16 - ADDITIONAL INFORMATION

HMIS Fire Hazard: 1
HMIS Health Hazard: 2*
HMIS Reactivity: 0
HMIS Personal Protection: X

MSDS Creation Date: 05/16/1995
MSDS Revision Date: 01/29/2009
MSDS Revision Notes: Format Update

Disclaimer: Reasonable care has been taken in the preparation of this information, but the

manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or

consequential damages resulting from its use.

Copyright© 1996-2008 Actio Software Corporation. All Rights Reserved.