

**Material Safety Data Sheet  
For Coatings, Resins and Related Materials**

Manufacturer's Name:  
Vimasco Corporation, P.O. Box 516, Nitro, W.Va. 25143

Emergency Phone  
(304) 755-3328

Date of Preparation: Updated (X)      Revised ( )  
August 9, 2002      New ( )

Information Phone  
(304) 755-3328

**Section I - Product Identification**

Product Number: THICK-KOTE

Product Name: Vinyl Mastic Weather Barrier

Product Class: Latex Based Coating (Mixture)

Transportation Information: Shipping Class, Paint, Class 55 - non hazardous (no special labels required)

**Section I I- Hazardous Ingredients**

<b>Ingredient</b>	<b>Percent By Weight</b>	<b>Occupational Exposure Limits TLV</b>	<b>Vapor Pressure</b>
Vinyl Acetate [108-05-4]	0.2%	10ppm(TWA-ACGIH)	Not Available

None of these ingredients is listed by OSHA, NTP, or IARC as a suspect or proven carcinogen.

**Section III - Physical Data**

Boiling Range: 212°F – 216°F

Vapor Density: Lighter than air

pH: 8.0 to 9.0

Evaporation Rate: Slower than ether

Volatile Volume: 35% to 40%

Wt/Gal: 10.5 lbs.

Specific Gravity: 1.26

Solubility in Water: Appreciable

Freezing Point: 25°F (-4°C)

Viscosity: Approximately 75,000 centipoises (spray grade); approximately 1,500,000 centipoises (trowel grade)

Decomposition Temperature: Approximately 240°F (115°C)      VOC: 38.5 g/l –water ( .32 lb/gal –water)

**Section IV - Fire and Explosion Hazard Data**

Flammability Classification: Flash Point: No flash to boiling 212°F (TCC); OSHA - IIIB; DOT - Not regulated  
LEL: Not available

Extinguishing Media: Foam, Alcohol Foam, CO<sub>2</sub>, Dry Chemical, Water Fog

Unusual Fire and Explosion Hazards: None known

Special Firefighting Procedure: Product will not burn until water has boiled or evaporated. For dried film or residual solids, full protective equipment is recommended, including self-contained breathing apparatus.

We believe the information here is current as of the date of this MSDS. Please study it carefully and apply appropriate engineering controls and industrial hygiene practices. As the conditions of use of this product and information are not within our control, it is the user's obligation to determine the conditions of safe use

**Section V - Health Hazard Data**

A TLV for this mixture has not been established. Therefore, the following effects of overexposure are those of the components listed in Section II.

**Vinyl Acetate & Acrylate (residual monomer):** Slight residual monomer can cause eye and respiratory irritation at high air concentrations. Vinyl acetate, in relatively high doses, is carcinogenic in experimental animals.

Medical Conditions Prone to Aggravation by Exposure: None known Primary Routes of Entry: Dermal or Inhalation

Emergency and First Aid Procedure: *Skin:* wash with soap and water. *Eyes:* flush with clean water at least 15 minutes. If irritation persists, consult physician. *Inhalation:* remove to fresh air. If breathing is difficult, administer oxygen. If irritation persists, consult physician. *Ingestion:* give two glasses of water, induce vomiting, consult physician or poison control center. ***Never give anything by mouth to an unconscious person.***

**Section VI - Reactivity Data**

Stability: Stable Hazardous Polymerization: Will not occur Conditions to avoid: None known

Hazardous Decomposition Products: Thermal decomposition will yield CO, CO<sub>2</sub>, and fragmented short-chain hydrocarbons.

Incompatibility (Materials to Avoid): Materials incompatible with water.

**Section VII - Spill or Leak Procedures**

Steps to be Taken in Case Material is Released or Spilled: Major spills should be collect for disposal. Minor spills may be flushed to sewer if regulations permit. Before drying, product may be washed away with water; after drying, remove with a paint scraper, or strong solvent.

Waste Disposal Method: In accordance with all applicable regulations. Review hazard section of this sheet before attempting cleanup. Empty containers are non hazardous under RCRA as industrial waste.

**Section VIII - Safe Handling and Use Information**

Respiratory Protection: In restricted ventilation areas, use approved chemical vapor respirator. In applications where mists or spray may be generated, avoid inhalation of airborne particulates by using an approved respirator with organic vapor cartridge with prefilter for mist or dust.

Ventilation: General (mechanical) room ventilation is expected to be satisfactory. Other Protective Equipment: None

Protective Gloves: Impervious gloves Eye Protection: Goggles, faceshield, or other eye wear to protect from splash.

Hygienic Practices: Thoroughly cleanse hands after handling. Launder contaminated clothing before reuse.

**Section IX - Special Precautions**

Precautions to be Taken in Handling and Storing: Avoid breathing vapors and application to hot surfaces, as vapor may be irritating. Keep container closed. Use with adequate ventilation. Store indoors at temperatures of 45°F to 90°F.

Other Precautions: For Industry/professional use only. Not intended for retail sale or use by individual consumers. Do not reuse container for potables or edibles.

**Section X - Sara Status**

This mixture contains the following materials regulated under Section 313:

NONE

We believe the information here is current as of the date of this MSDS. Please study it carefully and apply appropriate engineering controls and industrial hygiene practices. As the conditions of use of this product and information are not within our control, it is the user's obligation to determine the conditions of safe use.