EASY-CAULK RTV 919 (WATER)

NEUTRAL CURE PAINTABLE
100% SILICONE SEALANT

1-PART HIGH PERFORMANCE INDUSTRIAL / CONSTRUCTION GRADE SILICONE SEALANT

SPECIFIC APPLICATIONS

Recommended for use wherever future paintability is a concern, but can also be used in applications requiring water clean-up and low odor. This product is designed to eliminate the use of water-based sealants such as latex, acrylic latex and siliconized acrylic where cracking and shrinkage are a major concern and/or problem.

KEY PROPERTIES

Paintable, Water Clean-up, Low Odor, Mildew Resistant, No shrinkage or Cracking

PHYSICAL PROPERTIES

Cure System	Neutral /Water
Physical Properties (cured)	Rubber
Specific Gravity	1.05
Extrusion Rate, g/min.	400
Temperature Range	-62° to 200° F
Intermittent Temperature Range	220° F
Skin Over Time (min)	20 *
Tack Over Time (min)	50 *
Cure Time (hours)	24
Tensile Strength (psi)	150
Elongation %	900
Durometer Shore A	23
Dielectric Strength kv/mm (v/mil)	18 (500)
Dielectric Constant at Hz	2.7 @ 96
Shelf Life (months)	12

* All properties derived from lab conditions, (77° F at 50% relative humidity)

LIMITATIONS

Not for continuous underwater use. Not for structural glazing. Not for use on food contact surfaces. Not for medical use.

MEETS SPECIFICATIONS: NA

AVAILABLE COLORS: White
(Custom Colors Available Upon Request)

PACKAGING: 10.3 fl. oz. cartridges
5 gallon pails
55 gallon drums
Custom packaging

SILCO INC.
Application Driven Silicones