

RAINBOW (ACETOXY)

MULTI - COLORED

1-PART INDUSTRIAL / CONSTRUCTION
GRADE SILICONE SEALANT

SPECIFIC APPLICATIONS

This multi-colored silicone sealant is an excellent choice for use as a sealant or an adhesive when there is no need for cosmetic concerns. This product is available because of a production overrun which occurs during our color change process. Therefore, color will vary from cartridge to cartridge. All other physical characteristics will remain the same. This product is solvent-free, non flammable, environmentally safe, and thus has no shrinkage or cracking.

PHYSICAL PROPERTIES

Cure System	Acetoxy
Physical Properties (cured)	Rubber
Specific Gravity	1.04
Extrusion Rate, g/min.	330
Temperature Range	-62° to 400° F
Intermittent Temperature Range	450° F
Skin Over Time (min)	10*
Tack Over Time (min)	20*
Cure Time (hours)	24*
Tensile Strength (psi)	363
Elongation %	640
Durometer Shore A	26
Dielectric Strength (v/mm (v/mil))	20 (500)
Dielectric Constant at Hz	2.9 @ 60
Shelf Life (months)	12

* All properties derived from lab conditions, (77° F at 50% relative humidity)

MEETS SPECIFICATIONS: TT-S-001543A, TT-S-00230C, ASTM C 920

AVAILABLE COLORS: Blended colors in no specific order
(Clear, White, Black, Aluminum, Almond,
Bronze, Brown, Green, Yellow, Red)

PACKAGING: 10.3 fl. oz. cartridges
5 gallon pails
55 gallon drums
Custom packaging



SILCO INC.
Application Driven Silicones