


ALPHA ASSOCIATES, INC.

145 LEHIGH AVENUE LAKEWOOD, N.J. 08701
Phone: (732) 634-5700 Fax: (732) 634-1430

ALPHA - MARITEX
STYLE FCF-1000



DESCRIPTION

Alpha Maritex Style FCF-1000 is a lightweight fluorocarbon coated fiberglass fabric designed to provide the fabricator of small removable blankets with a supple, extremely flexible fabric for intricate shapes. The coating is highly resistant to most industrial chemicals and can be used in applications to 500 °F.

APPLICATIONS

Removable Blankets for Insulation
Small Valves and Fittings

ADVANTAGES

Good Chemical Resistance
Abrasion Resistant
Low Smoke Level
Good Flame Resistance

PROPERTY DATA STYLE FCF-1000

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<u>ENGLISH</u>	<u>METRIC</u>
WEIGHT	ASTM-D-3776	10 oz/sy \pm 10%	340 g/m ² \pm 9 g/m ²
THICKNESS	ASTM-D-1777	0.008" \pm .001"	0.203 mm \pm .025 mm
TENSILE STRENGTH	ASTM-D-5034	Warp- 190 lbs/in. Fill- 130 lbs/in.	33.93 kg/cm 23.22 kg/cm
TRAPEZOIDAL TEAR	ASTM-D-5587	Warp- 14 lbs Fill- 12 lbs	6.35 kg 5.44 kg
FLAMMABILITY	FED 191/5903.2	Char Length 1 inch maximum Afterglow 1 second maximum Flame Out 1 second maximum	2.54 cm max. 1 second maximum 1 second maximum
TEMPERATURE RESISTANCE	FED SPEC HHB-100B	-150 °F to 500 °F	-101 °C to 260 °C
BASE FABRIC and WEAVE		Satin Weave Fiberglass	
COLOR and COATING		Gray Fluorocarbon	
POROSITY		.01 CFM	

DATA SHEET 13293

REV C

DATE: 10/15/08

* All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.